

ST
LE™
AC
BK DATA

TECK
TAPE™



www.slabteck.com

Last Updated: 11/25/2025

Description

TECKTape by SlabTECK is an advanced low-VOC, water-based, acrylic engineered to bond with low-surface energy (LSE) films in all conditions and climates ensuring a proper seal, integrus seams, well-booted penetrations, and an overall ASTM E1643-compliant installation.

Installation

Install per:

- Project Specifications
- Local building codes
- ASTM E 1643
- SlabTECK Instructions

*Use lastest versions

TECKTape can be used in conjunction with TECK2BND reversible tape and TECKSeal sealant as essential accessories to ANY AND ALL polyolefin-based under-slab membrane installations. SlabTECK accessories are especially designed for use with TECKFilm under-slab membranes. For best results, install above freezing. If below 32 ° F, wipe surface clear of frost, oils, and other debris.

Performance and Attributes

Property	Value	Standard
Width	3"	--
Length	180'	--
Guage	PE Backing: 4-mils	ASTM D6988
	Adhesive: 2-mils	
180 Peel	18 oz	PSTC 101

Designed for the challenging construction environment.

Bonding with LSE films in cold and wet conditions can be difficult. TECKTape is up to the task. Engineered to bond to difficult surfaces, TECKTape's advanced, low VOC, acrylic adhesives are puros-built for the rugged under-slab environment, pre- and post- concrete placement. Our semi-direct approach minimizes middlemen and our integrated manufacturing allows our right-zized TECKTape to be offered without extra material, waste, and cost.

Current:
Data
Videos
Specs

